

PET FILMS: Non-Toxic * 100% Recyclable * PVC Alternative



Eco-friendly and specifically engineered for Thermoforming Applications.

- Superior Clarity
- Good Thermoforming Properties
- Superior Product Protection
- Hi-Impact Resistance
- Hi-Resistance to Cracking

Conversion: *We convert to Custom Sizes.* Test steel rule for effectiveness prior to cutting.

Compliance: FDA Approved, Phthalate Free, REACH, RoHS, TCPH (CONEG)

Sizes: .20 mm (.008") to 1.7 mm (.070") / Stock widths and Custom Sizes available.

Printing: OUV Ideal, Accepts FUV, DUV, DSO, SUV, SSO & Foil Stamping.

Adhesives: UV Curable or Solvent Adhesives, PU Hot Melt

Uses: Thermoform packaging, Clamshells, Trays, Blisters, Displays and Molds.



A-PET Forming Grades:

Clear Gloss/Gloss Film

BT802: Anti-Block, NO Silicone

BT835: Anti-Block & Anti-Static

BT864: Silicone Two Sides

BT834: Anti-Block & Silicone One Side

BE835: ESD (Static Dissipative Function)

Composition: 100% Virgin APET Resin, Clear Blue Tint. Anti-Slip Formulation.

RPET Forming Grades:

RECYCLED Clear Gloss/Gloss Film

BT021: Anti-Block. NO Silicone

BT035: Anti-Static

BT034: Anti-Block & Silicone One Side

BT064: Silicone Two Sides

Composition: 100% Post Industrial Recycled Content / Post Consumer by Late 2010/Early 2011

GRG Forming Grades:

BT240 Clear Gloss/Gloss film:

RF Weldable

Composition: 85% Post Industrial Recycled Content/ Anti-Blocking with Silicone. Also available in No Silicone Anti-Block version

GAG Forming Grades:

BT243 Clear Gloss/Gloss film:

RF Weldable

Composition: 100% Virgin Resin, Anti-Blocking with Silicone.

PVC RIGID VINYL FILMS



Specifically engineered for Thermoforming Applications.

- Superior Clarity
- Excellent Printability
- Hi-Impact Resistance
- Easy to Die Cut

Conversion: *We convert to Custom Sizes.*

Uses: Thermoform packaging, Clamshells, Trays, Blisters, Displays and Molds.

PVC Vacuum Form IG-4 Clear Gloss/Gloss film: RF Weldable

Composition: 100% Virgin Resin, Silicone Coated, Clear Blue Tint. Deep Draw available for custom orders.

Compliance: Phthalate Free, BPA Free, REACH, RoHS, TCPH (CONEG), DMF & PFOS Free

Sizes: .19 mm (.0068") to .60 mm (.024") / Stock widths and Custom Sizes available.

Printing: OUV Ideal, Accepts FUV, DUV, DSO, SUV, SSO & Foil Stamping.

Adhesives: Sonic, UV Curable or Solvent Adhesives

Print Legend:

OFFSET, UV Ink Systems: OUV
FLEXO, UV Ink Systems: FUV

DIGITAL, UV Ink Systems: DUV
DIGITAL, Solvent Ink Systems: DSO

SCREEN PRINT, UV Ink Systems: SUV
SCREEN PRINT, Solvent Ink Systems: SSO